



S118

The S118 Subwoofer is the companion subwoofer to the S7. The enclosure is loaded with a light weight, long excursion, 18" ND18-S Kevlar Neodymium driver utilizing Adamson's Advanced Cone Architecture and a 4" voice coil for exceptional power handling. It is mounted in an ultra-efficient front-loaded enclosure, designed to reproduce clean, musical low frequency information.

The cabinet construction uses marine grade birch plywood as well as aircraft grade steel and aluminum, and is equipped with Speakon™ NL4 connectors. The integrated rigging system matches the rigging for the S7 and can be flown in the same array without the need for an adapter frame. The S118 also comes with a built-in M20 thread on the top of the cabinet for pole mounting.

Specifications

Frequency Range (+/- 3dB)	35 Hz - 100 Hz
Maximum Peak SPL **	133 dB
Components LF	ND18-S 18" Kevlar Neodymium Driver
Nominal Impedance LF	8 Ω
Power Handling (AES / Peak) LF	500 / 2000 W
Rigging	Slidelock Rigging System Built-in M20 Thread
Connection	5x Speakon™ NL4: 2x Front (Pins 2 +/-), 2x Rear (Pins 1 +/-), 1x Rear Output (Pin 2 to Pin 1)
Height Front (mm / in)	508 / 20
Width (mm / in)	527 / 20.75
Depth (mm / in)	495 / 19.5
Weight (kg / lbs)	31 / 68.4
Supported Processing	Lake

**12 dB crest factor pink noise at 1m, half space, using specified processing and amplification

