









W8 W

8" A/W SPEAKER, WHITE (PAIR) [100V|8Ω]

-  Low Impedance Input
-  100V Line Input
-  Ver./Hor. Installation
-  Easy Install
-  Bracket Included
-  Discreet Design

The W8 all-weather two-way loudspeakers with built-in 100V transformer and 8Ω power tap are perfect for both distributed and near-field applications in environments such as retail stores, restaurants, bars, churches and gyms. The low frequencies are reproduced by a 8" direct-radiating woofer with a polypropylene cone, while the high-frequency section is based on a titanium tweeter. The speaker's design with a waveguide improves dynamics and efficiency bringing out details in everything you listen to, while reducing reflections that can color the sound. A U-bracket is included and will support your installation on the wall or ceiling.

Product Type

2-Way All-Weather Passive Speaker
(8Ω/100V)

Frequency Response (-6dB)

60Hz - 20kHz

Nominal Coverage (-6dB)

100° H x 100° V

RMS Power

60W

Program Power

120W

Nominal Impedance

8Ω (low impedance mode)

Sensitivity (1W, 1m)

94dB

Maximum SPL (calculated)

114.8dB

Transformer Taps 100V

10W | 20W | 30W | 40W

Low Frequency Driver

8" Polypropylene Cone Woofer

High Frequency Driver

1" Silk Dome Tweeter

Input Connectors

Binding Posts

Recommended Amplifier

A200 | MX120 | MX350

Grille

Aluminum Acoustically Invisible

Construction

UV Stabilised High Grade Polypropylene

IP Rating

IP55

Dimensions (WxHxD)

250 x 410 x 260mm (9.8 x 16.1 x 10.2 in)
[W8] | 250 x 410 x 290mm (9.8 x 16.1 x 11.4 in)
[W8 + U-Bracket]

Fixation

Wall U-Bracket (included)

Net Weight

5.8kg (12.79lb) [W8 + U-Bracket]

Shipping Weight

15kg (33.07lb)